

CURLOPT\_TLSAUTH\_USERNAME(3)    curl\_easy\_setopt options    CURLOPT\_TLSAUTH\_USERNAME(3)

## NAME

CURLOPT\_TLSAUTH\_USERNAME – user name for TLS authentication

## SYNOPSIS

```
#include <curl/curl.h>
```

```
CURLcode curl_easy_setopt(CURL *handle, CURLOPT_TLSAUTH_USERNAME, char *user);
```

## DESCRIPTION

Pass a char \* as parameter, which should point to the zero terminated username to use for the TLS authentication method specified with the *CURLOPT\_TLSAUTH\_TYPE(3)* option. Requires that the *CURLOPT\_TLS\_PASSWORD(3)* option also be set.

## DEFAULT

NULL

## PROTOCOLS

All TLS-based protocols

## EXAMPLE

TODO

## AVAILABILITY

Added in 7.21.4

## RETURN VALUE

Returns CURLE\_OK if the option is supported, CURLE\_UNKNOWN\_OPTION if not, or CURLE\_OUT\_OF\_MEMORY if there was insufficient heap space.

## SEE ALSO

CURLOPT\_TLSAUTH\_TYPE(3), CURLOPT\_TLSAUTH\_PASSWORD(3),